

DEVELOPMENT OF SWITCHABLE PLANAR REFLECTORS FOR BEAM
SHAPING REALIZATION

MUHAMMAD INAM ABBASI

A thesis submitted in
fulfillment of requirement for the award of
Doctor of Philosophy



Faculty of Electrical and Electronic Engineering
Universiti Tun Hussein Onn Malaysia

AUGUST 2016

Sincerely dedicated to my beloved Mother and Father...



ACKNOWLEDGEMENT

Deep and humble gratitude to ALLAH Almighty for providing the opportunity and giving me the strength to complete this work.

I would like to express heartiest thanks to my supervisor Assoc. Prof. Dr. Muhammad Yusof Ismail whose encouragement, guidance and continuous support enabled me to carry out this research work.

I would like to acknowledge Ministry of Higher Education, Malaysia for funding this research work under Prototype Research Grant Scheme (PRGS VOT0904) and Best Fundamental Research Grant Scheme (FRGS VOT0983).

My sincere thanks to the staff of Wireless and Radio Science Centre (WARAS), Universiti Tun Hussein Onn Malaysia (UTHM), The Institute of Space Science (ANGKASA) and Department of Electrical, Electronic & Systems Engineering (JKEES), Universiti Kebangsaan Malaysia (UKM) for providing technical facilities for this work.

Most importantly I would like to thank my parents, my sisters, my brother, my wife and other family members and friends in Pakistan and Malaysia for supporting me spiritually throughout this work and my life in general.

ABSTRACT

This work provides an extensive analysis for the design and performance optimization of planar reflectors within X-band and Ku-band frequency ranges. The objective of this work was to investigate the feasibility of using strategic slot embedded patch element configurations for an efficient reconfigurable reflectarray antenna design. PIN diodes were incorporated with single and multiple slot embedded patch element configurations for the design of beam switchable planar reflectors. Moreover unit cells based on liquid crystal substrates were also designed for comparison between two reconfigurable planar reflector design techniques. 3Dimensional electromagnetic computer models of CST Microwave Studio and Ansoft HFSS were used for the simulations and the results of unit cells were practically verified by waveguide scattering parameter measurements using vector network analyzer. Performance characterization for bandwidth and reflection loss optimization of different slot embedded patch configurations was done based on the scattering parameter measurements. Maximum frequency variation of 2.56GHz with dynamic phase range of 346° in X-band was demonstrated by rectangular slots in the centre and circular slots along width configuration while Ku-band measured results demonstrated a maximum frequency variation of 2.54GHz with dynamic phase range of 278° for circular slot with gap configuration. The measured scattering parameter results for the PIN diodes based elements designed in X-band frequency range are shown to provide a maximum frequency tunability of 0.55GHz with 238° of dynamic phase range in the case of embedded rectangular slots in the centre of patch element. On the other hand liquid crystal based embedded rectangular slots unit cells designed in X-band frequency range are shown to demonstrate comparatively lesser frequency tunability of 0.12GHz with dynamic phase range of 103° . Although liquid crystal based design is shown to offer good frequency tunability and dynamic phase range, however the loss associated with liquid crystals is one of the limitations of this design. Higher tunable loss factor of 1.91dB was demonstrated by liquid crystal

based design as compared to tunable loss factor of 1.43dB shown by PIN diode based design. The investigations were further extended by carrying out equivalent circuit analysis of PIN diode based and liquid crystal based designs for detailed characterization of reconfigurable planar reflector designs. Equivalent circuit model is demonstrated to offer a very close agreement between the simulated and scattering parameter measured results where a maximum discrepancy of 0.1dB was observed. A comprehensive mathematical model based on Finite Element Method (FEM) was proposed for progressive phase distribution to develop a novel design technique to create a reconfigurable reflectarray antenna based on strategic slot configurations. The developed model permits the positioning of an individual element of the array, required for progressive phase distribution, independent of its geometrical structure. Furthermore the developed algorithm can be used for both centre fed and off-set fed planar reflector designs while incorporating the effect of material properties of conductor and substrate. Three novel robust periodic reflectarray configurations, consisting of 144, 64 and 36 elements respectively were designed and fabricated for far-field radiation pattern measurements. The measured radiation patterns are shown to offer close agreement with the predicted results where switchable array based on PIN diodes confirmed a beam switching of $+6^\circ$, 0° and -6° while the passive 144, 64 and 36 elements arrays are observed to give maximum 3dB beamwidth of 10.5° , 11.4° and 13.2° respectively.



LIST OF PUBLICATIONS AND AWARDS

Following is the list of publications and awards achieved in the result of research presented in this work.

Publications

Book

- [1] M. Y. Ismail and M. Inam, *Reflectarray Antennas for Strategic Defense Technology*, UTHM Publisher, 2012 (ISBN 978-967-0468-01-3).

International Refereed Journals

- [2] M. Inam, M. Y. Ismail and M. Amin, “*Active Reflectarray Antennas: A Practical Approach for Comparison between PIN Diodes and Liquid Crystal Technology*”. Submitted to International Journal of Antennas and Propagation, April 2016.
- [3] M. Y. Ismail, M. Inam and F. Mohamed, “*Broadband Reflectarray Antenna based on Highly Conductive Graphene*”. Submitted to Microwave and Optical Technology letters, April 2016.
- [4] M. Inam and M. Y. Ismail, “*Analysis of Slotted Patch Elements for Phase Agile Reflectarray Antenna Design*”. Submitted to ARPN Journal of Engineering and Applied Sciences, April 2016.
- [5] M. Inam, M. Y. Ismail and M. Amin, “*X-band Frequency Switchable Reflectarray Antenna Using PIN Diodes*”. Submitted to Journal of Applied Research and Technology, December 2015.
- [6] M. Y. Ismail and M. Inam, “*Equivalent Circuit Modelling of Active Reflectarray Antenna*”. International Journal of Electrical, Computer, Energetic, Electronic and Communication Engineering Vol.10, No.6, pp. 631-635, 2016.
- [7] M. Y. Ismail and M. Inam, “*Liquid Crystal Based Reconfigurable Reflectarray Antenna Design*”. International Journal of Electrical, Computer, Energetic, Electronic and Communication Engineering Vol. 10, No.1, pp. 52-56, 2016.

- [8] M. Y. Ismail and M. Inam, “*Design of Liquid Crystal Based Tunable Reflectarray Antenna Using Slot Embedded Patch Element Configurations*”. International Journal of Electrical, Robotics, Electronics and Communications Engineering, Vol. 8, No. 10, pp. 1313-1318, 2014.
- [9] M. Y. Ismail, M. Inam and M. H. Dahri, “*Phase Characterization of Reconfigurable Reflectarray Antennas*”. International Journal on Electrical Engineering and Informatics, Vol. 5, No. 4, pp. 447-453, 2013.
- [10] M. Y. Ismail, M. Inam and A. F. M. Zain, “*Mathematical Model for Progressive Phase Distribution of Ku-band Reflectarray Antennas*”. International Journal of Electrical, Robotics, Electronics and Communications Engineering, Vol. 7, No. 12, 1226 – 1230, 2013.
- [11] M. Inam and M. Y. Ismail, “*Analytical Model and Practical Validation of Phase Variation of Reflectarray Antenna*”. Procedia Engineering, Elsevier, Vol. 53, pp. 225-232, 2013.
- [12] M. Y. Ismail and M. Inam, “*Resonant Elements for Tunable Reflectarray Antenna Design*” International Journal of Antennas and Propagation, Vol. 2012, Article ID 9148686, pages 6, 2012.
- [13] M. Inam and M. Y. Ismail, “*Reflection Loss and Bandwidth Performance of X-Band Infinite Reflectarrays: Simulations and Measurements*”. Microwave and Optical Technology letters, Vol. 53, No. 1, pp. 77-80, 2011.

Proceeding papers

International Conferences

- [14] M. Y. Ismail and M. Inam, “Equivalent Circuit Modelling of Active Reflectarray Antenna”. Accepted for presentation at 18th International Conference on Applications of Wireless and Optical Communications (ICAWOC 2016), Paris, France, June 2016.
- [15] M. Y. Ismail and M. Inam, “Liquid Crystal Based Reconfigurable Reflectarray Antenna Design”. International Conference on Electrical, Computer, Electronics and Communication Engineering (ICECECE2016), Istanbul, Turkey, January 2016.
- [16] M. Y. Ismail and M. Inam, “Development of Switchable Planar Reflectors for Beam Shaping Realization”. Fourth International conference on Aerospace and Engineering (ICASE), Islamabad, Pakistan, September, 2015

- [17] M. Y. Ismail and M. Inam, "An Efficient Progressive Phase Distribution Consideration of Reflectarray Antennas". The 36th Progress in Electromagnetics Research Symposium (PIERS), Czech Republic, European Union, July, 2015.
- [18] M. Y. Ismail and M. Inam, "Design of Liquid Crystal Based Tunable Reflectarray Antenna Using Slot Embedded Patch Element Configurations". XII International Conference on Electrical, Computer, Electronics and Communication Engineering (ICECECE2014), Bali, Indonesia, October 2014.
- [19] M. Y. Ismail and M. Inam, "Characterization of Resonant Elements for Passive and Reconfigurable Reflectarray Design", IEEE International Conference on Intelligent and Advanced Systems (ICIAS 2014), Kuala Lumpur, Malaysia, June 2014.
- [20] M. Y. Ismail, M. Inam and A. F. M. Zain, "Mathematical Model for Progressive Phase Distribution of Ku-band Reflectarray Antennas". International Conference on Electrical, Computer, Electronics and Communication Engineering (ICECECE 2013), Phuket, Thailand, December 2013.
- [21] M. Inam, M. Y. Ismail and A. F. M. Zain, "Multi-State Frequency Switchable Reflectarray Antenna Design". IEEE International Conference on Space Science and Communication (IconSpace 2013), July 2013, Melaka, Malaysia.
- [22] M. Inam and M. Y. Ismail, "Integration of PIN Diodes with Slot Embedded Patch Elements for Active Reflectarray Antenna Design". IEEE International Symposium on Telecommunication Technologies (ISTT 2012), November 2012, Kuala Lumpur, Malaysia.
- [23] M. Inam and M. Y. Ismail, "Analytical Model of Progressive Phase Distribution of Reflectarray Antenna". The 31st Progress In Electromagnetics Research Symposium (PIERS 2012), March, 2012, Kuala Lumpur, Malaysia.
- [24] M. Y. Ismail, M. Inam, M. H. Dahri, "Performance Optimization of Reconfigurable Reflectarray Antennas". The 28th International Review of Progress in Applied Computational Electromagnetics (ACES 2012) April 2012, Columbus, Ohio, U.S.A.
- [25] M. Y. Ismail, M. Inam, N. H. Sulaiman and M. A. Mughal, "Slotted Tunable Reflectarray Antenna". 2011 Asia-Pacific Microwave Conference (APMC 2011), December 2011, Melbourne, Australia.
- [26] M. Y. Ismail and M. Inam and M. H. Dahri and N. H. Sulaiman, "Reconfigurable Reflectarray Antennas: An Alternative Novel Solution for



Satellite Communication Systems”. The 9th International Conference on Frontiers of Information Technology (FIT), December 2011, Islamabad, Pakistan.

- [27] M. Inam and M. Y. Ismail, “Slot Elements for Tunable Reflectarray Antenna Design”. 2011 Malaysian Technical Universities International Conference on Engineering & Technology (MUiCET 2011), November 2011, Batu Pahat, Malaysia.

Local Conferences

- [28] M. Y. Ismail and M. Inam, “Tunable Reflectarray Antenna for Beam Steering Applications”. Seminar Hasil Penyelidikan, AKEPT, January 2015, Negeri Sembilan, Malaysia.
- [29] M. Inam, M. Y. Ismail and A. F. M. Zain, “X-Band Frequency Switchable Planar Reflector using PIN Diodes”. Malaysian Technical Universities Conference on Engineering and Technology (MUCET), December 2013, Pahang, Malaysia.
- [30] M. Y. Ismail and M. Inam, “Performance Characterization of Passive and Active Reflectarray Antennas”. Seminar Hasil Penyelidikan, AKEPT, November 2012, Negeri Sembilan, Malaysia.

Awards

- [1] “Best Research Project Presentation at WARAS Postgraduate Colloquium”, University Tun Hussein Onn Malaysia (UTHM), Johor, Malaysia, May 2016.
- [2] Gold Medal for “Miniaturized Dual Frequency Planar Antenna for Radio Systems”, at 2012 Seoul International Invention Fair (SIIF 2012), Dec 2012, COEX Hall, Gangnam Gu Korea.
- [3] Special Prize Award by the Korean Invention Association for “Miniaturized Dual Frequency Planar Antenna for Radio Systems”, at 2012 Seoul International Invention Fair (SIIF 2012), Dec 2012, COEX Hall, Gangnam Gu Korea.
- [4] Gold Medal for “Dual Frequency Flat Reflector for Mobile Communication Systems”, 23rd International Invention, Innovation & Technology Exhibition (ITEX 2012), May 2012, Kuala Lumpur, Malaysia.

- [5] Gold Medal for “Miniaturized Dual Frequency Planar Array”, 11th Malaysia Technology Expo (MTE 2012), The Invention and Innovation Awards, February 2012, Kuala Lumpur, Malaysia.
- [6] Special Diamond Medal Award for the category “International Invention of the year” for the invention “Multi-Function Tunable Broadband Flat Antenna”, British Invention Show (BIS 2011), Old Spitalfields, London, United Kingdom, October 2011.
- [7] Gold Medal for “Multi-Function Tunable Broadband Flat Antenna”, British Invention Show (BIS 2011), Old Spitalfields, London, United Kingdom, October 2011.
- [8] Gold Medal for “Progressive Phase Distribution Analysis of Reflectarray Antennas”, 2011 Research and Innovation Competition (R&I compete 2011), November 2011 UTHM, Johor, Malaysia.

Patents of Research Products

M. Y. Ismail, M. Inam and N. H. Sulaiman, “Miniaturized Dual Frequency Planar Array”. PI 2012700925 (Patent Pending).



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CONTENTS

ACKNOWLEDGEMENT	iv
ABSTRACT	v
LIST OF PUBLICATIONS AND AWARDS	vii
CONTENTS	xii
LIST OF TABLES	xvi
LIST OF FIGURES	xviii
CHAPTER 1 INTRODUCTION	1
1.1 Problem statement	3
1.2 Objectives of the research	4
1.3 Scopes of the research	4
1.4 Conceptual background of planar reflectors	5
1.5 Advantages and disadvantages of planar reflector antennas	7
1.5.1 Advantages of planar reflectors	7
1.5.2 Disadvantages of planar reflectors	10
1.6 Flow of the thesis	12
CHAPTER 2 BACKGROUND AND RESEARCH OVERVIEW	14
2.1 Parabolic reflectors	15
2.2 Phased array antennas	16
2.3 Planar reflectors	19
2.3.1 Basic design and analysis techniques of planar reflectors	21
2.3.2 Passive planar reflectors	27
2.3.3 Reconfigurable planar reflectors	31
2.4 Conclusion	39



PT TAAUTHM
PERPUSTAKAAN TUN ABDUL RAZAK

CHAPTER 3	RESEARCH FRAMEWORK	40
3.1	CST MICROWAVE STUDIO simulations	43
3.2	Ansoft HFSS simulations	46
3.3	Equivalent circuit analysis	50
3.4	Numerical modelling of planar reflectors	52
3.5	Fabrication of planar reflectors	53
3.6	Measurement procedures	53
3.7	Conclusion	55
CHAPTER 4	DESIGN AND ANALYSIS OF PASSIVE PLANAR REFLECTORS UNIT CELLS	56
4.1	Passive unit cell planar reflector design	56
4.2	Slot configurations for reconfigurable planar reflector design	58
4.3	X-band passive unit cell measurements and analysis	59
4.3.1	Rectangular slots in centre of patch elements	62
4.3.2	Circular slots in centre of patch elements	64
4.3.3	Rectangular slot in centre and along length of patch	65
4.3.4	Rectangular slot in centre and circular slots along width of patch	67
4.3.5	Performance characterization	69
4.4	Ku-band passive unit cell measurements and analysis	70
4.4.1	Rectangular slot in centre with gap	70
4.4.2	Circular slot in centre with gap	72
4.5	Conclusion	74
CHAPTER 5	DESIGN AND ANALYSIS OF ACTIVE PLANAR REFLECTORS UNIT CELLS	75
5.1	Design of active planar reflector unit cell	75



5.1.1	Design validation: Liquid crystal based active reflectarray	76
5.1.2	Frequency switchable planar reflector using PIN diodes	78
5.2	Multi-state frequency switchable planar reflector design	86
5.2.1	Rectangular slots in centre and along length with pin diodes	87
5.2.2	Ku-band planar reflector design	90
5.3	Frequency switchable planar reflector with progressive phase distribution	92
5.3.1	X-band planar reflector design	93
5.3.2	Ku-band planar reflector design	97
5.4	Slot and gap embedded active patch elements	99
5.4.1	X-band planar reflector unit cells	99
5.4.2	Ku-band design	101
5.4.3	Dynamic phase range enhancement of Ku-band designs	103
5.5	Equivalent circuit modelling of active planar reflectors	106
5.5.1	Equivalent circuit of passive planar reflector	107
5.5.2	Equivalent circuit analysis of PIN diodes based design	108
5.5.3	Equivalent circuit analysis of liquid crystal based design	112
5.6	Fabrication and measurements of active unit cells	116
5.6.1	Active planar reflectors unit cells using PIN diodes	116
5.6.2	Active planar reflectors unit cells using liquid crystals	120
5.6.3	Comparative summary	125



5.7	Conclusion	126
CHAPTER 6	MODELLING AND DEVELOPMENT OF COMPLETE PERIODIC PLANAR REFLECTORS	128
6.1	Mathematical modelling for progressive phase distribution	128
6.1.1	Analysis for general design of planar reflectors	129
6.1.2	Effect of material properties on progressive phase distribution	133
6.1.1	Periodic array design using different dielectric materials	135
6.1.2	Periodic planar reflector design using mathematical modelling	139
6.1.3	Subtended half angle and phase distribution gradient	142
6.1.4	Validation of the proposed mathematical model	144
6.2	Slot embedded patch elements periodic reflectarray design	146
6.2.1	Passive reflectarray antenna design	146
6.2.2	Active reflectarray antenna design	156
6.3	Far-field measurements	159
6.3.1	Passive reflectarray antenna	159
6.3.2	Active reflectarray antenna	163
6.4	Conclusion	166
CHAPTER 7	CONCLUSIONS AND FUTURE DIRECTIONS	168
7.1	Discussion of results	168
7.2	Recommendations for future work	172
	REFERENCES	175
	APPENDIX A	181



PTTA AUTHM
PERPUSTAKAAN TUNKU AMINAH

LIST OF TABLES

Table 2.1: Performance of different element shapes [46]	30
Table 2.2: Properties of some of the liquid crystals used for reconfigurable reflectarray design at 10GHz	33
Table 2.3: Selected technologies for the implementation of reconfigurable reflectarrays and qualitative assessment of a few related properties	38
Table 2.4: Performance comparison of different reflectarray antenna designs	39
Table 3.1: Design specifications for planar reflector at 10GHz with ΔS variation	49
Table 4.1: Comparison of different characteristics of proposed designs	69
Table 5.1: Properties of different liquid crystal dielectric substrates	76
Table 5.2: Comparison and summary of LC based design results	78
Table 5.3: Summary of the results for reconfigurable planar reflector design using different PIN diodes	84
Table 5.4: Frequency tunability for different slot configurations used with PIN diodes	86
Table 5.5: Resonant frequency and reflection loss for different PIN diode states	89
Table 5.6: Comparison of frequency tunability and dynamic phase range in X-band and Ku-band	92
Table 5.7: Resonant frequency and reflection loss X-band frequency switchable planar reflector	94
Table 5.8: Summary of the results for proposed planar reflector design	96
Table 5.9: Summary of gap and slot embedded design results	103
Table 5.10: Effect of gap variation on Ku-band frequency switchable planar reflector design	104

Table 5.11: Values of lumped components for PIN diode embedded planar reflector unit cell	110
Table 5.12: Lumped component values for liquid crystal based design at different applied voltages	114
Table 5.13: Frequency tunability and dynamic phase range for different fabricated samples	120
Table 5.14: Comparison of frequency tunability and dynamic phase range for different design configurations of liquid crystal based planar reflector unit cells	123
Table 5.15: Measured performance comparison between the PIN diodes and liquid crystal base planar reflector design	126
Table 5.16: General comparison between the PIN diodes and liquid crystal base planar reflector design	126
Table 6.1: Material properties and calculated values of x at 10GHz	135
Table 6.2: Values of C and K for different materials at 10GHz	136
Table 6.3: Values of C and K for different materials for a planar reflector design at 15.2GHz	137
Table 6.4: FoM for different materials used in X-band and Ku-band frequency ranges	139
Table 6.5: Comparison of simulated results between f/D ratio of 0.5 and 0.9	151
Table 6.6: Material properties and performance comparison of reflectarrays designed with different dielectric materials	155
Table 6.7: Comparison between proposed design and different designs from literature	155
Table 6.8: Comparison between reflectarrays designed with APD 0805-000 and MA4GP907 PIN diodes	159
Table 6.9: Comparative summary of measured and simulated far-field radiation pattern results	161
Table 6.10: Fabrication error calculated for 8x8 array	163



LIST OF FIGURES

Figure 1.1: (a) A typical parabolic reflector operation (b) Principle of operation for an n element variable size microstrip reflectarray	5
Figure 1.2: Phase distribution of reflectarrays (a) No phase distribution technique applied (b) Effective phase distribution technique applied for planar wavefront	7
Figure 1.3: Reflectarray on a house wall for DBS [26]	8
Figure 2.1: Evolution of planar reflectors for high gain beam steering applications	14
Figure 2.2: Different forms of parabolic reflector (a) Parabolic right cylinder and (b) Paraboloid [29]	15
Figure 2.3: Parabolic reflector with different feeds (a) Front feed (b) Cassegrain feed	16
Figure 2.4: L-band dipole phased-array test bed [33]	17
Figure 2.5: Schematic of a typical phased array antenna [33]	18
Figure 2.6: Phased array with optical signal processing beam forming network [35]	19
Figure 2.7: (a) Unit cell reflectarray patch element of (b) Reflection loss curve at resonant frequency of 10GHz	20
Figure 2.8: Reflection phase curve for a reflectarray resonant at 10 GHz	21
Figure 2.9: Reflectarray design with variable size patches [28]	21
Figure 2.10: Differential spatial phase delay of reflectarray antenna	22
Figure 2.11: Total electric field for a unit cell patch element reflectarray [37]	23
Figure 2.12: (a) Inter element spacing d in a reflectarray (b) Radiation pattern of a reflectarray (E-plane) [38]	24
Figure 2.13: Dielectric absorption in dielectric layer of reflectarray	26
Figure 2.14: A multilayer design of reflectarray proposed for bandwidth enhancement [41]	28

Figure 2.15: Periodic cell of reflectarray elements [42]	28
Figure 2.16: An EBG structure for patch element unit cell [45]	29
Figure 2.17: (a) Copper pads etched on the slot. (b) RF MEMS switches mounted on the copper pads on the slot (c) S-band scattering parameter measurement set-up [14]	32
Figure 2.18: Concept of the active planar reflector based on liquid crystals [11]	34
Figure 2.19: Measured E-plane far-field patterns at 34 GHz [55]	35
Figure 2.20: Reconfigurable folded reflectarray based on liquid crystal [56]	35
Figure 2.21: Design of a C-band electronically beam scanning aperture coupled reflectarray [18]	36
Figure 2.22: Radiation pattern of reflectarray for different scanned beams [60]	38
Figure 3.1: Sequential stages of the project	40
Figure 3.2: Complete flow chart of the research work	42
Figure 3.3: Design of a unit cell in CST MWS with $\lambda/2$ inter-element spacing	44
Figure 3.4: Design of planar reflector unit cell in CST MWS at 10GHz	44
Figure 3.5: Direction of the excited electric fields	45
Figure 3.6: Geometry of the microstrip resonant patch element	45
Figure 3.7: Boundary conditions in CST MWS for infinite planar reflector	46
Figure 3.8: Model of an infinite planar reflector in Ansoft HFSS	47
Figure 3.9: Mesh generated by Ansoft HFSS for infinite planar reflector	48
Figure 3.10: A converged solution for a planar reflector designed at 10GHz	48
Figure 3.11: Runtime and number of passes required for different values of ΔS	49
Figure 3.12: Reflection loss curves for different values of ΔS	50
Figure 3.13: Structure of a simple parallel plate capacitor	51
Figure 3.14: Scattering parameter measurement set-up for unit cell planar reflector elements (a) complete set-up (b) close up view of coax-waveguide adapter (c) waveguide aperture	54
Figure 3.15: Far-field reflectarray antenna measurement set-up inside a 3m anechoic chamber and control station	55
Figure 4.1: Simulated results obtained by CST MWS and Ansoft HFSS (a) Reflection loss curves (b) Reflection phase curves	57
Figure 4.2: Surface current distribution for a rectangular patch of planar reflector	58

Figure 4.3: Scattering parameter measurements (a) Geometry of the unit cell patch element (b) Complete measurement set-up	60
Figure 4.4: Reflection loss curves for four different samples of ground planes	61
Figure 4.5: Different fabricated unit cells patch elements (a) Rectangular slots in centre of patch elements (b) Circular slots in centre of patch elements (c) Rectangular slot in centre and along length of patch elements (d) Rectangular slot in centre and circular slots along width of patch elements (e) Sample of a ground plane	62
Figure 4.6: Proposed design of rectangular slots in centre of patch elements (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	62
Figure 4.7: Comparison between simulated and measured results for rectangular slots embedded patch elements (a) Reflection loss (b) Reflection phase	63
Figure 4.8: Measured dynamic phase range ($\Delta\phi_d$) for rectangular slots in the centre of patch element	64
Figure 4.9: Proposed design of circular slots in centre of patch elements (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	64
Figure 4.10: Comparison between simulated and measured results for circular slots embedded patch elements (a) Reflection loss (b) Reflection phase	65
Figure 4.11: Proposed design of rectangular slots in centre and along length of patch (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	66
Figure 4.12: Comparison between simulated and measured results (a) Reflection loss (b) Reflection phase	66
Figure 4.13: Proposed design of rectangular slots in centre and circular slots along width of patch elements (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	68
Figure 4.14: Comparison between simulated and measured results for rectangular slots in centre and circular slots along width of patch elements (a) Reflection loss (b) Reflection phase	68

Figure 4.15: Ku-band design of rectangular slot in centre with gap configuration (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	71
Figure 4.16: Comparison between simulated and measured results of Ku-band rectangular slot and gap embedded elements (a) Reflection loss (b) Reflection phase	72
Figure 4.17: Ku-band design of circular slot and gap embedded patch elements (a) Detailed geometry (b) Surface current distribution (c) Fabricated unit cells	73
Figure 4.18: Comparison between simulated and measured results of Ku-band circular slot and gap embedded elements (a) Reflection loss (b) Reflection phase	73
Figure 5.1: Two patch element unit cell built model	77
Figure 5.2: Comparison between CST MWS and Ansoft HFSS results [11] for K15 liquid crystal substrate	77
Figure 5.3: ON and OFF states of a PIN Diode	79
Figure 5.4: Frequency switchable planar reflector using a rectangular slot and a PIN diode	80
Figure 5.5: Reflection loss for different states of PIN diodes with rectangular slots in centre of patch	81
Figure 5.6: Reflection phase for different states of PIN diodes with rectangular slots in centre of patch	81
Figure 5.7: Effect of PIN diode resistance variation on the resonant frequency and reflection loss of planar reflector	82
Figure 5.8: Effect of PIN diode capacitance variation on surface current density and electric field intensity of planar reflector unit cell	83
Figure 5.9: Effect of PIN diode capacitance variation on the resonant frequency and reflection loss of planar reflector	83
Figure 5.10: Frequency switchable planar reflector using a circular slot and a PIN diode	85
Figure 5.11: Reflection loss for different states of PIN diodes with circular slots in centre of patch	85
Figure 5.12: Reflection phase for different states of PIN diodes with circular slots in centre of patch	86

Figure 5.13: Unit cell element with three rectangular slots and three PIN diodes	87
Figure 5.14: Reflection loss curves for different states of PIN diodes	88
Figure 5.15: Reflection phase curves for different states of PIN diodes	89
Figure 5.16: Electric field intensity and surface current density for different PIN diode states	90
Figure 5.17: Reflection loss curves for different PIN diode states using circular slot configurations in Ku-band	91
Figure 5.18: Reflection phase curves for different PIN diode states using circular slot	91
Figure 5.19: Unit cell of a frequency switchable planar reflector with progressive phase distribution	93
Figure 5.20: Reflection loss curves for X-band frequency switchable planar reflector (a) PIN diode Off (b) PIN diode ON	94
Figure 5.21: Reflection phase curves for X-band frequency switchable planar reflector (a) PIN diode Off (b) PIN diode ON	95
Figure 5.22: Progressive phase distribution for two states at 10GHz	96
Figure 5.23: Reflection loss curves for Ku-band frequency switchable planar reflector (a) PIN diode Off (b) PIN diode ON	97
Figure 5.24: Reflection phase curves for Ku-band frequency switchable planar reflector (a) PIN diode Off (b) PIN diode ON	98
Figure 5.25: Circular slot in the centre of patch element with gap	99
Figure 5.26: Surface current distribution for circular slot with gap	100
Figure 5.27: Reflection loss and reflection phase curves for the circular slot and gap	100
Figure 5.28: Surface current distribution for rectangular slot with gap	101
Figure 5.29: Reflection loss and reflection phase for the rectangular slot and gap	101
Figure 5.30: Reflection loss and reflection phase curves for Ku-band circular slot switchable planar reflectors	102
Figure 5.31: Reflection loss and reflection phase curves for Ku-band rectangular slot switchable planar reflectors	103
Figure 5.32: Effect of substrate thickness on reflection phase of frequency switchable planar reflectors	105



Figure 5.33: Comparison of X-band and Ku-band results for different substrate thicknesses	106
Figure 5.34: Equivalent circuit model for a typical reflectarray	107
Figure 5.35: Equivalent circuit model for a PIN diode embedded planar reflector unit cell	109
Figure 5.36: Equivalent circuit representation of PIN diode based design	111
Figure 5.37: Comparison between equivalent circuit and simulated results based on CST MWS (a) reflection loss and (b) reflection phase curves	111
Figure 5.38: Comparison and discrepancy between the reflection losses	112
Figure 5.39: Liquid crystal based design of planar reflector and its equivalent circuit representation	113
Figure 5.40: Equivalent circuit for LC based resonant element of planar reflector	114
Figure 5.41: Comparison between Ansoft HFSS, equivalent circuit and measured results	115
Figure 5.42: Equivalent circuit of an NxN element liquid crystal based active planar reflector	116
Figure 5.43: Fabricated unit cell, biasing circuit and complete measurements set-up	117
Figure 5.44: Comparison between measured and simulated reflection losses for PIN diode embedded active planar reflector unit cells	118
Figure 5.45: Comparison between measured and simulated reflection phases for PIN diode embedded active planar reflector unit cells	119
Figure 5.46: Different LC based design configurations (a) Rectangular patch (b) Rectangular patch with rectangular slot (c) Rectangular patch with circular slot	120
Figure 5.47: Liquid crystal based planar reflector unit cells (a) Fabricated unit cell patch elements and LC cavities (b) Rectangular patch, Rectangular slot embedded patch, Circular slot embedded patch and back side of complete unit cell assembly in encapsulator (c) LC filling in cavity, complete measurement set-up and unit cell inserted in waveguide for scattering parameter measurements	121



Figure 5.48: Comparison between measured and simulated reflection loss and reflection phase curves (a) rectangular patch element (b) Rectangular patch with rectangular slot (c) Rectangular patch with circular slot element	122
Figure 5.49: Effect of different voltage levels on liquid crystal based planar reflector unit cell performance (a) Reflection loss and (b) Reflection phase	124
Figure 5.50: Trend of measured frequency tunability and dynamic phase range at different voltage levels for rectangular slot embedded patch element	124
Figure 5.51: Step wise and total time consumed for setting of liquid crystal for different increasing and decreasing voltage levels	125
Figure 6.1: Required phase shift at reflectarray surface using ray tracing [73]	131
Figure 6.2: Reflection phase from different feed points in a planar reflector	132
Figure 6.3: Reflection phase curves for progressive phase distribution of planar reflectors with different feed positions	132
Figure 6.4: Effects of different material properties on the reflection phase of planar reflector design	134
Figure 6.5: Effect of different material properties on the reflection phase obtained for different feed positions	134
Figure 6.6: Reflection phase curves for planar reflectors modelled with different substrates at 10GHz	137
Figure 6.7: Reflection phase curves for planar reflectors modelled with different substrates at 15.2 GHz	138
Figure 6.8: Required reflection phase for (a) 8x8 element planar reflector array (b) 12x12 element planar reflector array (c) 15x15 element planar reflector array	140
Figure 6.9: Required Reflection phase curves for a planar reflector (8x 8 elements) (a) with different feed positions (b) $f = f_0$ (Centre feed) (c) $f = f_0 - \lambda$ (d) $f = f_0 + \lambda$ (e) $f = f_0 - 1/2 \lambda$ (f) $f = f_0 + 1/2 \lambda$	141
Figure 6.10: Subtended half angle in a planar reflector	142
Figure 6.11: (a) Linear static phase range for different sizes of arrays (b) Phase distribution gradient	143

Figure 6.12: Simulated reflection phase curves and reflection phase values of different widths of rectangular slots at 10 GHz	144
Figure 6.13: (a) Design of a planar reflector with elements placed according to mathematical modelling required phase. Comparison of required and simulated phase for (b) 8x8 array (c) 12x12 array (d) 15x15 array (e) phases for different feed positions	145
Figure 6.14: 3D view and schematic diagram of the designed reflectarray antenna	147
Figure 6.15: Absolute electric Field intensity and surface current density on the designed 12x12 element reflectarray	147
Figure 6.16: Absolute electric field intensity and surface current density on the ground plane of designed reflectarray	148
Figure 6.17: Simulated power for reflectarray antennas with different number of array elements at 10GHz ($f/D=0.5$)	149
Figure 6.18: Maximum power radiated by reflectarray antenna at different frequencies ($f/D=0.5$)	149
Figure 6.19: Radiated power for reflectarray with different f/D ratios at 10GHz	150
Figure 6.20: Simulated power for reflectarray antennas with different number of array elements at 10GHz ($f/D=0.9$)	150
Figure 6.21: Maximum power radiated by reflectarray antenna at different frequencies ($f/D=0.9$)	151
Figure 6.22: Co-polar and cross-polar components for a 12x12 array at 10GHz	153
Figure 6.23: Effect of substrate thickens on reflectarray antenna performance	154
Figure 6.24: Effect of different materials on the radiated power of 12x12 element reflectarray antenna design at 10GHz	154
Figure 6.25: Proposed design (a) Close up view of unit cell (b) built model of 12x12 active reflectarray antenna	156
Figure 6.26: Far-field patterns of proposed reflectarray antennas with and without PIN diodes at 10GHz	157
Figure 6.27: Radiation pattern for initial and switched beams for 12x12 element active reflectarray antenna at 10GHz	158



REFERENCES

- [1] D. Berry, R. Malech, and W. Kennedy, "The Reflectarray Antenna," *IEEE Trans. Antennas Propag.*, vol. 11, no. 6, pp. 645–651, 1963.
- [2] J. Huang and J. A. Encinar, "Overview of Analysis Techniques," in *Reflectarray Antennas*, Wiley Inter Science, 2007, pp. 29–34.
- [3] J. A. Encinar, M. Arrebola, M. Dejus, and C. Jouve, "Design of a 1-metre Reflectarray for DBS Application with 15% Bandwidth," in *2006 First European Conference on Antennas and Propagation*, 2006, pp. 1–5.
- [4] S. V. Hum, S. Member, and J. Perruisseau-carrier, "Reconfigurable Reflectarrays and Array Lenses for Dynamic Antenna Beam Control: A Review," *IEEE Trans. Antennas Propag.*, vol. 62, no. 1, pp. 183–198, 2014.
- [5] J. Huang, "Microstrip Reflectarray," in *Antennas and Propagation Society Symposium 1991 Digest*, 1991, pp. 612–615.
- [6] D. M. Pozar and T. Metzler, "Analysis of a Reflectarray Antenna using Microstrip Patches of Variable Size," *Electron. Lett.*, vol. 29, no. 8, pp. 657–658, 1993.
- [7] M. Y. Ismail and M. Inam, "Performance Improvement of Reflectarrays Based on Embedded Slots Configurations," *Prog. Electromagn. Res.*, vol. 14, pp. 67–78, 2010.
- [8] J. Huang and R. J. Pogorzelski, "Microstrip Reflectarray with Elements Having Variable Rotation Angles," *IEEE, AP-S Symp. Dig.*, vol. 2, pp. 1280–1283, 1997.
- [9] B. Strassner, C. Han, and K. Chang, "Circularly polarized Reflectarray with Microstrip Ring Elements having Variable Rotation Angles," *Antennas Propagation, IEEE Trans.*, vol. 52, no. 4, pp. 1122–1125, 2004.
- [10] S. V. Hum, M. Okoniewski, and R. J. Davies, "Realizing an Electronically Tunable Reflectarray using Varactor Diode-tuned Elements," *IEEE Microw. Wirel. Components Lett.*, vol. 15, no. 6, pp. 422–424, 2005.
- [11] M. Y. Ismail, W. Hu, R. Cahill, V. F. Fusco, H. S. Gamble, D. Linton, R. Dickie, S. P. Rea, and N. Grant, "Phase Agile Reflectarray Cells Based on

- Liquid Crystals,” *Microwaves, Antennas Propagation, IET*, vol. 1, no. 4, pp. 809–814, 2007.
- [12] W. Hu, M. Y. Ismail, R. Cahill, H. S. Gamble, R. Dickie, V. F. Fusco, D. Linton, S. P. Rea, and N. Grant, “Tunable Liquid Crystal Reflectarray Patch Element,” *Electron. Lett.*, vol. 42, no. 9, p. 509, 2006.
 - [13] A. Moessinger, R. Marin, J. Freese, S. Mueller, A. Manabe, and R. Jakoby, “Investigations on 77 GHz Tunable Reflectarray Unit Cells with Liquid Crystal,” in *2006 First European Conference on Antennas and Propagation*, 2006, pp. 1–4.
 - [14] H. Rajagopalan, Y. Rahmat-Samii, and W. A. Imbriale, “RF MEMS Actuated Reconfigurable Reflectarray Patch-Slot Element,” *Antennas Propagation, IEEE Trans.*, vol. 56, no. 12, pp. 3689–3699, 2008.
 - [15] F. A. Tahir, H. Aubert, and E. Girard, “Equivalent Electrical Circuit for Designing MEMS-controlled Reflectarray Phase Shifters,” *Prog. Electromagn. Res.*, vol. 100, pp. 1–12, 2010.
 - [16] L. Boccia, F. Venneri, G. Amendola, and G. Di Massa, “Experimental Investigation of a Varactor Loaded Reflectarray Antenna,” in *2002 IEEE MTT-S International Microwave Symposium Digest Cat No02CH37278*, 2002, vol. 1, pp. 69–71.
 - [17] S. V. Hum, M. Okoniewski, and R. J. Davies, “Modeling and Design of Electronically Tunable Reflectarrays,” *IEEE Trans. Antennas Propag.*, vol. 55, no. 8, pp. 2200–2210, 2007.
 - [18] M. Riel and J. J. Laurin, “Design of an Electronically Beam Scanning Reflectarray using Aperture-coupled Elements,” *IEEE Trans. Antennas Propag.*, vol. 55, no. 5, pp. 1260–1266, 2007.
 - [19] Malagasi. C. S, “Microstrip Dics Element Refelctarray,” in *Aerospace system Conv*, 1978, pp. 186–192.
 - [20] J. Munson, R. E, Haddad, H. and Hanlen, “Microstrip Refelctarray Antenna for Sattellite Communication and Radar Cross-Section Enhancement or Reduction,” U.S. Patent No. 4684952, Washington D. C., 1987.
 - [21] R. D. Javor, X. D. Wu, and K. Chang, “Design and Performance of a Microstrip Reflectarray Antenna,” *IEEE Trans. Antennas Propag.*, vol. 43, no. 9, pp. 932–939, 1995.
 - [22] K. Y. Sze and L. Shafal, “Analysis of Phase Variation Due to Varying Patch Length in a Microstrip Reflectarray,” in *IEEE Antennas and Propagation Society International Symposium*, 1998, vol. 2, pp. 1134–1137.

- [23] D. M. Pozar, S. D. Targonski, and H. D. Syrigos, "Design of Millimeter Wave Microstrip Reflectarrays," *IEEE Trans. Antennas Propag.*, vol. 45, no. 2, pp. 287–296, 1997.
- [24] J. Huang, "Capabilities of Printed Reflectarray Antennas," in *Proceedings of International Symposium on Phased Array Systems and Technology*, 1996, pp. 131–134.
- [25] J. Huang, "Analysis of Microstrip Reflectarray Antenna for Microspacecraft Applications," *TDA Prog. Rep. 42-120*, pp. 153–173, 1995.
- [26] J. A. Encinar, M. Arrebola, L. F. De La Fuente, and G. Toso, "A transmit-receive Reflectarray Antenna for Direct Broadcast Satellite Applications," *IEEE Trans. Antennas Propag.*, vol. 59, no. 9, pp. 3255–3264, 2011.
- [27] P. Dreyer, M. Morales-masis, and S. Nicolay, "Copper and Transparent-Conductor Reflectarray Elements on Thin-Film Solar Cell Panels," *IEEE Trans. Antennas Propag.*, vol. 62, no. 7, pp. 3813–3818, 2014.
- [28] J. Huang and J. A. Encinar, *Reflectarray Antennas*. Wiley Inter Science, 2007.
- [29] C. A. Balanis, *Antenna Theory: Analysis and Design*, 3rd ed. John Wiley and sons, 2005.
- [30] P. J. B. Clarricoats, "High Efficiency Microwave Reflector Antennas- A Review," *Proc. IEEE*, vol. 65, no. 10, pp. 1470–1502, 1977.
- [31] O. Hachenberg, B. H. Grahl, and R. Wielebinski, "The 100-Meter Radio Telescope at Effelsberg," in *Proceedings of the IEEE*, 1973, vol. 61, no. 9.
- [32] A. Mrstik, "Scan Limits of Off-Axis Fed Parabolic Reflectors," *IEEE Trans. Antennas Propag.*, vol. 27, no. 5, pp. 647–651, 1979.
- [33] A. J. Fenn, D. H. Temme, W. P. Delaney, and W. E. Courtney, "The Development of Phased-Array Radar Technology," *Physics (College. Park. Md.)*, vol. 12, no. 2, pp. 321–340, 2000.
- [34] N. Kingsley, G. E. Ponchak, and J. Papapolymerou, "Reconfigurable RF MEMS Phased Array Antenna Integrated Within a Liquid Crystal Polymer (LCP) System-on-Package," *IEEE Trans. Antennas Propag.*, vol. 56, no. 1, pp. 108–118, 2008.
- [35] T. Akiyama, K. Inagaki, and Y. Mizuguchi, "Beam-Steering and Multibeam Formation of Ku-band Phased Array Antenna using Optical Signal Processing Beam-Forming Network," in *International Topical Meeting on Microwave Photonics*, 1999, pp. 173–176.
- [36] D. M. Pozar, "Bandwidth of Reflectarrays," *Electron. Lett.*, vol. 39, no. 21, pp. 1490–1491, 2003.



- [37] M. Y. Ismail and M. Inam, *Refelctarray Antennas for Strategic Defense Technology*. Penerbit UTHM, 2012.
- [38] D. Pilz and W. Menzel, "Full Wave Analysis of a Planar Reflector Antenna," *Proc. 1997 Asia-Pacific Microw. Conf.*, vol. 1, 1997.
- [39] A. Soares, S. Fonseca, and A. Giarola, "Surface Wave Excitation on a Microstrip Ring Antenna," *IEEE Trans. Antennas Propag.*, vol. 37, no. 10, pp. 137–140, 1989.
- [40] C. James, J. R., Hall, P. S. and Wood, *Microstrip Antenna Theory and Design*. IEE Electromagnetic Wave Series 12. Peter Pregrinus Ltd., 1981.
- [41] J. A. Carrasco, E., Alfageme, B., and Encinar, "Design of a Multilayer Aperture-Coupled Cell Used as Phase Shifter in Reflectarrays," in *Proc. Journe'es Internationales de Nice sur les Antennes*, 2004, pp. 194–197.
- [42] V. F. Misran, N., Cahill, R. and Fusco, "Concentric Split Ring Element for Dual Frequency Reflectarray Antennas," *Electron. Lett.*, vol. 39, no. 25, pp. 1176–1177, 2003.
- [43] F. Yang, Y. Kim, J. Huang, and A. Elsherbeni, "Design and Fabrication of a Folding-and-rolling Reflectarray Antenna," in *2007 IEEE Antennas and Propagation Society International Symposium*, 2007, pp. 1–4.
- [44] K. M. Shum, Q. Xue, C. H. Chan, and K. M. Luk, "Investigation of Microstrip Reflectarray using a Photonic Bandgap Structure," *Microw. Opt. Technol. Lett.*, vol. 28, no. 2, pp. 114–116, 2001.
- [45] H. Liu, B. Wang, X. Yang, and W. Shao, "Elimination of Mutual Couplings In Reflectarray using Electromagnetic Bandgap Structures," in *2006 IEEE Antennas and Propagation Society International Symposium*, 2006, pp. 1–4.
- [46] M. Bozzi, S. Germani, and L. Perregrini, "A Figure of Merit for Losses in Printed Reflectarray Elements," *IEEE Antennas Wirel. Propag. Lett.*, vol. 3, no. 1, pp. 257–260, 2004.
- [47] A. A. Bosh, "Effect of the Conductive Coating Thickness on Performance of Microstrip Reflectarray," *Microw. Opt. Technol. Lett.*, vol. 51, no. 5, pp. 1288–1290, 2009.
- [48] O. Bayraktar, O. A. Civi, and T. Akin, "Beam Switching Reflectarray with MEMS Controls," in *Antennas and Propagation EuCAP 2010 Proceedings of the Fourth European Conference on*, 2010, vol. 1, pp. 1–4.
- [49] L. Marcaccioli, S. Montori, R. V Gatti, E. Chiuppesi, P. Farinelli, and R. Sorrentino, "RF MEMS Reconfigurable Architectures for Very Large Reflectarray Antennas," in *2009 Asia Pacific Microwave Conference*, 2009, pp. 766–769.

- [50] H. Rajagopalan, Y. Rahmat-Samii, and W. A. Imbriale, "Reconfigurable Patch-Slot Reflectarray Elements using RF MEMS Switches: A Subreflector Wavefront Controller," in *2007 IEEE Antennas and Propagation Society International Symposium*, 2007, pp. 1–4.
- [51] E. Lueder, *Liquid Crystal Displays: Addressing Schemes and Electro-optical Effects*, 2nd ed. John Wiley and Sons, 2010.
- [52] J. Goodby, P. J. Collings, T. Kato, C. Tschierske, H. Gleeson, and P. Raynes, *Handbook of Liquid Crystals*, 2nd ed. John Wiley and Sons, 2014.
- [53] A. Moessinger, S. Dieter, W. Menzel, S. Mueller, and R. Jakoby, "Realization and Characterization of a 77GHz Reconfigurable Liquid Crystal Reflectarray," in *2009 13th International Symposium on Antenna Technology and Applied Electromagnetics and the Canadian Radio Science Meeting*, 2009, pp. 1–4.
- [54] S. Bildik, C. Fritzsche, A. Moessinger, and R. Jakoby, "Tunable Liquid Crystal Reflectarray with Rectangular Elements," in *German Microwave Conference 2010*, 2010, vol. 8, no. c, pp. 1–4.
- [55] J. R. Mossinger, A. Marin, R. Mueller, S. Freese, "Electronically Reconfigurable Reflectarrays with Nematic Liquid Crystals," *IET Electron. Lett.*, vol. 42, no. 16, pp. 899–900, 2006.
- [56] S. Bildik, S. Member, S. Dieter, C. Fritzsche, W. Menzel, and R. Jakoby, "Reconfigurable Folded Reflectarray Antenna Based Upon Liquid Crystal Technology," *IEEE Trans. Antennas Propag.*, vol. 63, no. 1, pp. 122–132, 2015.
- [57] M. E. Bialkowski and H. J. Song, "Dual Linearly Polarized Reflectarray using Aperture Coupled Microstrip Patches," in *IEEE Antennas and Propagation Society International Symposium 2001*, 2001, vol. 3, pp. 486–489.
- [58] M. E. Bialkowski and H. J. Song, "Investigations into a Power-Combining Structure using a Reflectarray of Dual-Feed Aperture-coupled Microstrip Patch Antennas," *IEEE Trans. Antennas Propag.*, vol. 50, no. 6, pp. 841–849, 2002.
- [59] V. Fusco, "Mechanical Beam Scanning Reflectarray," *IEEE Trans. Antennas Propag.*, vol. 53, no. 11, pp. 3842–3844, 2005.
- [60] M. R. Chaharmir, J. Shaker, M. Cuhachi, and A. Sebak, "Mechanically Controlled Reflectarray Antenna for Beam Switching and Beam Shaping in Millimetre-wave Applications," *Electron. Lett.*, vol. 39, no. 7, pp. 4–5, 2003.
- [61] J. A. Encinar, "Design of Two-layer Printed Reflectarrays using Patches of Variable Size," *IEEE Trans. Antennas Propag.*, vol. 49, no. 10, pp. 1403–1410, 2001.



- [62] E. Carrasco, M. Barba, and J. A. Encinar, "X-Band Reflectarray Antenna With Switching-Beam Using PIN Diodes and Gathered Elements," *IEEE Trans. Antennas Propag.*, vol. 60, no. 12, pp. 5700–5708, 2012.
- [63] D. C. Chang and M. C. Huang, "Multiple-polarization Microstrip Reflectarray Antenna with High Efficiency and Low Cross-polarization," *IEEE Trans. Antenna Propag.*, vol. 43, pp. 829–834, 1995.
- [64] M. Patel and J. Thraves, "Design and Development of a Low Cost, Electronically Steerable, X-band Reflectarray using Planar Dipoles," in *Proc. Of Military Microwaves*, 1994, pp. 174–179.
- [65] "CST MicroWave Studio®, [online: www.cst.com]." .
- [66] "Ansoft HFSS®, [online: www.ansys.com]." .
- [67] D. M Pozar, *Microwave Engineering*, 3rd. John Wiley and Sons, Inc., 2005.
- [68] M. Y. Ismail, M. Inam, and A. M. A. Zaidi, "Reflectivity of Reflectarrays Based on Dielectric Substrates," *Appl. Sci.*, vol. 3, no. 1, pp. 180–185, 2010.
- [69] "MULTISIM® [online: www.ni.com/multisim/]." .
- [70] "MATLAB®, [online: www.mathworks.com]." .
- [71] M. I. Abbasi and M. Y. Ismail, "Reflection Loss and Bandwidth Performance of X-band Infinite Reflectarrays: Simulations and Measurements," *Microw. Opt. Technol. Lett.*, vol. 53, no. 1, pp. 77–80, 2011.
- [72] M. Y. Ismail, M. I. Abbasi, A. F. M. Zain, M. Amin, and M. F. L. Abdullah, "Characterization of Loss and Bandwidth Performance of Reflectarray Antenna Based on Lumped Components," *Int. J. Electr. Electronics Informatics*, vol. 2, no. 2, pp. 113–122, 2010.
- [73] H. Rajagopalan, S. Xu, and Y. Rahmat-Samii, "Reflectarray Reflection Phase Diagnostics," in *2011 IEEE International Symposium on Antennas and Propagation APSURSI*, 2011, pp. 1636–1638.
- [74] E. Carrasco, J. A. Encinar, and M. Barba, "Bandwidth Improvement in Large Reflectarrays by Using True-Time Delay," *IEEE Trans. Antennas Propag.*, vol. 56, no. 8, pp. 2496–2503, 2008.
- [75] J. A. Encinar, C. Tienda, E. Carrasco, M. Arrebola, and G. Toso, "Design of Dual-reflectarray Antenna for Beam Scanning," in *Antennas and Propagation Society International Symposium APSURSI 2010 IEEE*, 2010, pp. 1–4.
- [76] M. Zhou;, O. Borries;, and E. Jorgensen, "Design and Optimization of a Single-Layer Planar Transmit-Receive Contoured Beam Refelctarray with Enhanced Performance," *IEEE Trans. Antennas Propag.*, vol. 63, no. 4, pp. 1247–1254, 2015.

